
Appendix M

Flow and Injection Testing Summary

This page intentionally left blank.

Appendix M.

Flow and Injection Testing Summary

Ormat performed a 46-day flow and injection test from April 27 to June 11, 2017. Locations of test wells, observation wells, springs, and faults are shown in **Figure M0**. Plots of production rates over time and injection rates over time are provided in **Figure M1-M3**.

Water was pumped from Well 23A-8, with discharge rates decreasing over time from approximately 2,080 to 1,340 gpm, with an average production rate of approximately 1,600 gpm (**Figure M1**). Production Well 23A-8 was drilled through densely compacted and cemented alluvial materials extending to 3,400 ft bgs and is completed in Triassic slate and siltstone in the footwall of the range-front fault at 4,733 ft bgs (**Table M1**). Permeable fractures associated with an east-northeast-striking fault zone were recorded in 23A-8 at depths of approximately 4,580 and 4,640 ft bgs (Ormat Fault Model, 2017).

Discharge water was reinjected at Wells 24-8 and 75-4, which are completed in mineralized and fractured alluvium at depths 3,060 ft bgs and 2,493 ft bgs, respectively (**Table M1**). Injection rates decreased over time at Well 24-8 from approximately 2,500 to 1,300 gpm (**Figure M2**), while the injection rate was relatively constant at Well 75-4 at an average of 165 gpm (**Figure M3**). The average injection rate was approximately 1350 gpm, with the variance between pumping and injection being mostly due to evaporative losses from holding tanks and temperature changes.

M.1 PRESSURE AND POTENTIOMETRIC HEAD OBSERVATIONS

Observation wells 23-8, 24A-8, 42-9, 86-7, and 22-8B were monitored for hydraulic head responses during testing activities to determine the degree of hydraulic connectivity between bedrock and deep mineralized/cemented alluvial aquifer, and to qualitatively assess fault permeabilities. Observation well depths and lithologies are summarized in **Table M1**. Plots of pressure head versus time are also included in **Figure M4-M8** and maximum observed hydraulic responses are summarized in **Table M2**.

Observation wells 86-7 and 22-8B are completed in densely compacted and cemented basin-fill. Decreases in pressure head in wells 86-7 and 22-8B (**Figure M6** and **Figure M7**) during the flow test indicate a hydraulic interconnection between the Pre-Tertiary bedrock and deep consolidated/cemented basin-fill. The pressure response observed at 86-7 suggests that the range-front fault and east-northeast trending faults between 86-7 and 23A-8 are permeable. Pressure data at well 24A-8 (**Figure M8**) is unclear whether the small (~1.5 psi) reduction in pressure head at this observation well was a response to the flow test.

Well 42-9 exhibited the greatest reduction in absolute pressure during the flow test, decreasing from 118.4 to 104.95 psi, but then gradually recovering back to the initial pressure after approximately 30 days (**Figure M5**). Well 42-9 is separated from production well 23A-8 by the regional range-front Dixie Valley and Piedmont faults and associated intra-basin faults; the hydraulic response observed at 42-9 suggests that pressure responses occur across these fault structures, which may be indicative of deep permeability across the fault planes. The presence of an observed deep pressure response to the east of Dixie Meadows, in conjunction with the lack of spring responses, especially at the high temperature springs NDOWSS-1 and 5A-5B within Dixie Meadows (Section M.2) supports the conceptual hydrogeological model that the source of thermal spring discharge is from the shallow lateral flow system defined by temperature-gradient data, and not the hypothesized upwelling along the Piedmont Fault. The pressure differential deep beneath Dixie Meadows would have otherwise intercepted potentiometric head driving spring discharge at the thermal springs. The observation that pressures returned to near the pre-test levels during the pumping and injection suggests that the pumping and injection was in relative balance and reporting predominantly to the deep aquifer system, and not the shallow lateral flow system.

M.2 SPRING POOL, TEMPERATURE AND EC OBSERVATIONS

Five spring locations were monitored for temperature, electrical conductivity (EC), and spring pool stage during flow testing activities to assess the degree of hydraulic connectivity between the geothermal reservoir and springs in Dixie Meadows. Monitoring locations are shown in Figure 14B. Plots of data collected by Ormat for the flow testing are included in **Figure M9** to **M23**.

Spring 5A-5B is the nearest to the production well (24A-8) and primary injection well (24-8) used in the 2017 flow test, and is situated in Dixie Meadows Spring Complex 3. Spring 5A-5B did not display any significant variances in temperature, spring pool height, or EC outside of what appears to be normal variations recorded before and after testing (**Figure M9** to **M11**). The low temperature during the testing period was 123°F, and the high was 130°F, being within the range of 104.8 to 139.77°F that is observed in the 2015-2020 period of record. There were no apparent influences of pumping and injection activities observed at this spring location.

Monitoring of spring pool stage, temperature, and EC at spring sites USGS-101 and Site 2 (Downstream of USGS-101) also appeared to have remained stable during the flow test (M12-M14, and M21 to M23). These springs are both located in Complex 1A and are cold water springs. Temperature and EC remained relatively constant over time at Spring 2 (Downstream of USGS 101), while EC increased mildly in May and June, and continued to rise after the test. The EC increase is likely due to increased evaporation during the summer months (**Figure M14**). Pool depth decreased and EC increased during the test and post-test and is likely the result of increasing summer temperatures and evapotranspiration. Temperature remained stable at 68.5 to 69.8 °F, which is consistent with the 2015-2020 period of record data .

Temperature and spring pool increases recorded at NDOWSS-1, the hottest spring in the Dixie Meadows, were mildly increasing during the flow test (**Figure M16**). The increases during the flow test appear to have been associated with the flow testing. The temperatures observed during the flow test ranged from 137 to 144.5°F. The 2015 to 2020 period of record range of temperature is 130.82 to 160.54°F, and the temperatures observed during testing were very near to the period of record average temperature of 141.87°F. Down-stream of NDOWSS-1 near the confluence point for spring discharge in Spring Complex 2 (labeled Spring 4 in the flow testing), the water stage, temperature and EC remained relatively constant during the monitoring period (**Figures M18-M20**).

In summary, the observations made during the flow test indicate little to no observed changes in spring discharge conditions within Spring Complexes 1, 2 and 3 in Dixie Meadows as a result of production and injection during the 2017 flow testing.

M.3 TRACER OBSERVATIONS

Return curves of tracers 2-ns and 2,6-nds, which were introduced into Wells 24-8 and 75-4, respectively, during flow/injection testing operations, are included in **Figures M24 to M25**. Well 24-8 was injecting return flows into compacted/cemented alluvial materials up to 3,060 ft bgs. Well 75-4 is completed in both dense compacted/cemented alluvium up to 2,493 ft bgs and granodiorite and gabbro to 5,000 ft bgs.

A valid tracer response typically maintains measurable concentrations for a period of time that depends on the amount and duration of tracer injected and the hydrogeologic conditions. The observed 2-ns returns at Production Well 23A-8 (**Figure M24**) indicate some injection fluid return to production due to a hydraulic connection between the deep cemented and fractured basin-fill and the underlying bedrock.

Isolated detections of very small quantities of tracer were observed at each spring, but these individual detections do not exhibit the appearance of a typical solute breakthrough curve, which would show sustained elevated

concentrations following an initial rise. These individual detections may instead be the result of cross-contamination from tracer-laden injectate encountered while conducting pump test operations and monitoring. Tracer detections for both 2-ns and 2,6-nds at Spring 2 (Below USGS-101, **Figure M27** and **M33**) occurred near the end of the flow test, but decline back toward non-detect values prior to the cessation of injection rather than exhibiting sustained breakthrough. These tracer detections likewise may have resulted from cross contamination.

In summary, the tracers added to the injection water indicated hydraulic connection between the 24-8 injection well and 24A-8 production well, but did not indicate a hydraulic connection between injection wells and spring sources that were monitored. Isolated positive detections are not consistent with a sustained subsurface connection between the injection well and the monitoring points.




FIGURE M0

TITLE:
**SITE MAP
 -SHOWING-
 MONITORING LOCATIONS DURING 2017 FLOW TEST**
 ORNI 32, LLC
 DIXIE MEADOWS GEOTHERMAL PROJECT
 CHURCHILL COUNTY, NV

JOB NO.:
ORM007

DATE:
5/24/2021


McGinley & Associates
 Environmental Engineering and Science
 RENO | LAS VEGAS | www.mcgin.com


FILE:
Fig 2 - Monitoring Locations During 2017 Flow Test

COORDINATE SYSTEM:
NAD 1983 UTM Zone 11N


| | | | | |
|----------|----|----------|----|-----------|
| DESIGNED | DS | CHECKED | DW | REVISION: |
| DRAWN | HC | APPROVED | DW | - |

This page intentionally left blank.



| | | | | | |
|---|---|--------------------------|--|--------------------------------|--|
|  McGinley & Associates Environmental Engineering and Science | Title Production Rate Over Time at 23A-8 During Flow Testing Operations | | | Figure M1 | |
| | Project Name Dixie Meadows | Project Number ORM007 | | | |
| | Client Name Ormat | Date 7/19/201 | | | |

Injection Rate Over Time at 24-8



Title **Injection Rate Over Time at 24-8 During Flow Testing Operations**

Project Name **Dixie Meadows**

Project Number **ORM007**


Figure

Client Name **Ormat**

Date **7/8/2019**

M2

Injection Rate Over Time at 75-4



Title **Injection Rate Over Time at 75-4 During Flow Testing Operations**

Project Name **Dixie Meadows**

Project Number **ORM007**


Figure

Client Name **Ormat**


Date **7/19/201**


M3

23-8 Pressure Over Time




| | | | | | |
|--------------|---------------|----------------|----------|--|-----------|
| Title | | | | Pressure Over Time at 23-8 During Flow Testing Operations | |
| Project Name | Dixie Meadows | Project Number | ORM007 | Figure | M4 |
| Client Name | Ormat | Date | 7/8/2019 | | |




| | | | |
|---|---|------------------------------|--------------------------------|
|  McGinley & Associates Environmental Engineering and Science | Title Pressure Over Time at 42-9 During Flow Testing Operations | | |
| | Project Name Dixie Meadows | Project Number ORM007 | Figure M5 |
| | Client Name Ormat | Date 7/8/2019 | |

86-7 Pressure Over Time




| | | | | | |
|--------------|---------------|----------------|----------|--|--|
| Title | | | | Pressure Over Time at 86-7 During Flow Testing Operations | |
| Project Name | Dixie Meadows | Project Number | ORM007 | Figure M6 | |
| Client Name | Ormat | Date | 7/8/2019 | | |

22-8B Water Levels Over Time




| | | | | | |
|--------------|---------------|----------------|----------|--|--|
| Title | | | | Hydrograph for 22-8B During Flow Testing Operations | |
| Project Name | Dixie Meadows | Project Number | ORM007 | Figure M7 | |
| Client Name | Ormat | Date | 7/8/2019 | | |

24A-8 Pressure Over Time




| | | | | | |
|--------------|---------------|----------------|----------|--|--|
| Title | | | | Pressure Over Time at 24A-8 During Flow Testing | |
| Project Name | Dixie Meadows | Project Number | ORM007 | Figure M8 | |
| Client Name | Ormat | Date | 7/8/2019 | | |

Water Depth for 5A/5B




| | | | |
|-----------------------------------|---------------|----------------|------------------|
| Title Water Depth at 5A/5B | | | |
| Project Name | Dixie Meadows | Project Number | ORM007 |
| Client Name | Ormat | Date | 3/9/21 |
| | | | Figure M9 |

Temperature for 5A/5B




| | | | |
|-----------------------------------|---------------|----------------|-------------------|
| Title Temperature at 5A/5B | | | |
| Project Name | Dixie Meadows | Project Number | ORM007 |
| Client Name | Ormat | Date | 3/9/21 |
| | | | Figure M10 |

Specific Conductivity for 5A/5B




| | | | |
|---|---------------|----------------|-------------------|
| Title Specific Conductivity at 5A/5B | | | |
| Project Name | Dixie Meadows | Project Number | ORM007 |
| Client Name | Ormat | Date | 3/9/21 |
| | | | Figure M11 |

Water Depth for Downstream of USGS 101




| | | | |
|--|---------------|----------------|-------------------|
| Title Water Depth at Downstream of USGS 101 | | | |
| Project Name | Dixie Meadows | Project Number | ORM007 |
| Client Name | Ormat | Date | 3/9/21 |
| | | | Figure M12 |

Temperature for Downstream of USGS 101




| | | | |
|--|---------------|----------------|-------------------|
| Title Temperature at Downstream of USGS 101 | | | |
| Project Name | Dixie Meadows | Project Number | ORM007 |
| Client Name | Ormat | Date | 3/9/21 |
| | | | Figure M13 |

Specific Conductivity for Downstream of USGS 101




| | | | |
|--|---------------|----------------|-------------------|
| Title Specific Conductivity at Downstream of USGS 101 | | | |
| Project Name | Dixie Meadows | Project Number | ORM007 |
| Client Name | Ormat | Date | 3/9/21 |
| | | | Figure M14 |

Water Depth for NDOWSS-1




| | | | |
|--------------------------------------|---------------|----------------|-------------------|
| Title Water Depth at NDOWSS-1 | | | |
| Project Name | Dixie Meadows | Project Number | ORM007 |
| Client Name | Ormat | Date | 3/9/21 |
| | | | Figure M15 |

Temperature for NDOWSS-1




| | | | |
|--------------------------------------|---------------|----------------|-------------------|
| Title Temperature at NDOWSS-1 | | | |
| Project Name | Dixie Meadows | Project Number | ORM007 |
| Client Name | Ormat | Date | 3/9/21 |
| | | | Figure M16 |

Specific Conductivity for NDOWSS-1




| | | | |
|--|---------------|----------------|-------------------|
| Title Specific Conductivity at NDOWSS-1 | | | |
| Project Name | Dixie Meadows | Project Number | ORM007 |
| Client Name | Ormat | Date | 3/9/21 |
| | | | Figure M17 |

Water Depth for Near Complex 2 Confluence




| | | | |
|---|---------------|----------------|-------------------|
| Title Water Depth at Near Complex 2 Confluence | | | |
| Project Name | Dixie Meadows | Project Number | ORM007 |
| Client Name | Ormat | Date | 3/9/21 |
| | | | Figure M18 |

Temperature for Near Complex 2 Confluence




| | | | |
|---|---------------|----------------|-------------------|
| Title Temperature at Near Complex 2 Confluence | | | |
| Project Name | Dixie Meadows | Project Number | ORM007 |
| Client Name | Ormat | Date | 3/9/21 |
| | | | Figure M19 |

Specific Conductivity for Near Complex 2 Confluence




| | | | |
|---|---------------|----------------|-------------------|
| Title Specific Conductivity at Near Complex 2 Confluence | | | |
| Project Name | Dixie Meadows | Project Number | ORM007 |
| Client Name | Ormat | Date | 3/9/21 |
| | | | Figure M20 |

Water Depth for USGS 101




| | | | |
|--------------------------------------|---------------|----------------|-------------------|
| Title Water Depth at USGS 101 | | | |
| Project Name | Dixie Meadows | Project Number | ORM007 |
| Client Name | Ormat | Date | 3/9/21 |
| | | | Figure M21 |

Temperature for USGS 101




| | | | |
|--------------------------------------|---------------|----------------|-------------------|
| Title Temperature at USGS 101 | | | |
| Project Name | Dixie Meadows | Project Number | ORM007 |
| Client Name | Ormat | Date | 3/9/21 |
| | | | Figure M22 |

Specific Conductivity for USGS 101




| | | | |
|--|---------------|----------------|-------------------|
| Title Specific Conductivity at USGS 101 | | | |
| Project Name | Dixie Meadows | Project Number | ORM007 |
| Client Name | Ormat | Date | 3/9/21 |
| | | | Figure M23 |

Return Curves for 2-ns (Injection at Well 24-8)




| | | | | |
|--------------|---------------|------------------------|---------|----------------------|
| Title | | Return Curves for 2-ns | | Figure M24 |
| Project Name | Dixie Meadows | Project Number | ORM007 | |
| Client Name | Ormat | Date | 4/26/21 | |

Return Curves for 2-ns (Injection at Well 24-8)




| | | | | | |
|--------------|---------------|----------------|---------|-------------------------------|--|
| Title | | | | Return Curves for 2-ns | |
| Project Name | Dixie Meadows | Project Number | ORM007 | Figure M25 | |
| Client Name | Ormat | Date | 4/26/21 | | |

Return Curves for 2-ns (Injection at Well 24-8)




| | | | | |
|--------------|---------------|-------------------------------|---------|----------------------|
| Title | | Return Curves for 2-ns | | Figure M26 |
| Project Name | Dixie Meadows | Project Number | ORM007 | |
| Client Name | Ormat | Date | 4/26/21 | |

Return Curves for 2-ns (Injection at Well 24-8)



| | | | | |
|--------------|---------------|-------------------------------|---------|----------------------|
| Title | | Return Curves for 2-ns | | Figure M27 |
| Project Name | Dixie Meadows | Project Number | ORM007 | |
| Client Name | Ormat | Date | 4/26/21 | |


Return Curves for 2-ns (Injection at Well 24-8)



McGinley & Associates
Environmental Engineering and Science


| | | | | |
|--------------|---------------|-------------------------------|---------|----------------------|
| Title | | Return Curves for 2-ns | | Figure M28 |
| Project Name | Dixie Meadows | Project Number | ORM007 | |
| Client Name | Ormat | Date | 4/26/21 | |

Return Curves for 2-ns (Injection at Well 24-8)



| | | | | |
|--------------|---------------|-------------------------------|---------|----------------------|
| Title | | Return Curves for 2-ns | | Figure M29 |
| Project Name | Dixie Meadows | Project Number | ORM007 | |
| Client Name | Ormat | Date | 4/26/21 | |


Return Curves for 2,6-nds (Injection at Well 75-4)



McGinley & Associates
Environmental Engineering and Science

| | | | | |
|--------------|---------------|----------------------------------|---------|----------------------|
| Title | | Return Curves for 2,6-nds | | Figure M30 |
| Project Name | Dixie Meadows | Project Number | ORM007 | |
| Client Name | Ormat | Date | 4/26/21 | |


Return Curves for 2,6-nds (Injection at Well 75-4)



McGinley & Associates
Environmental Engineering and Science


| | | | | |
|--------------|---------------|----------------------------------|---------|----------------------|
| Title | | Return Curves for 2,6-nds | | Figure M31 |
| Project Name | Dixie Meadows | Project Number | ORM007 | |
| Client Name | Ormat | Date | 4/26/21 | |

Return Curves for 2,6-nds (Injection at Well 75-4)




| | | | | |
|--------------|---------------|----------------------------------|---------|----------------------|
| Title | | Return Curves for 2,6-nds | | Figure M32 |
| Project Name | Dixie Meadows | Project Number | ORM007 | |
| Client Name | Ormat | Date | 4/26/21 | |

Return Curves for 2,6-nds (Injection at Well 75-4)




| | | | | |
|--------------|---------------|----------------------------------|---------|----------------------|
| Title | | Return Curves for 2,6-nds | | Figure M33 |
| Project Name | Dixie Meadows | Project Number | ORM007 | |
| Client Name | Ormat | Date | 4/26/21 | |

Return Curves for 2,6-nds (Injection at Well 75-4)



| | | | | |
|--------------|---------------|----------------------------------|---------|----------------------|
| Title | | Return Curves for 2,6-nds | | Figure M34 |
| Project Name | Dixie Meadows | Project Number | ORM007 | |
| Client Name | Ormat | Date | 4/26/21 | |

Return Curves for 2,6-nds (Injection at Well 75-4)



| | | | | |
|--------------|---------------|----------------------------------|---------|----------------------|
| Title | | Return Curves for 2,6-nds | | Figure M35 |
| Project Name | Dixie Meadows | Project Number | ORM007 | |
| Client Name | Ormat | Date | 4/26/21 | |

Table M1. Details for Existing Wells Near Dixie Meadows

| Well ID** | Well Owner | Completion Date | Easting (m) | Northing (m) | TOC Elevation (ft amsl) | Borehole Depth (ft bgs) | Cased Depth (ft bgs) | Borehole Diameter (in.) | Well Diameter (in.) | Top of screen (ft bgs) | Bottom of Screen (ft bgs) | Well Completion Geology | SWL (ft bgs) | GW Elevation (ft amsl) |
|-------------|----------------------------|-----------------|-------------|--------------|-------------------------|-------------------------|----------------------|-------------------------|---------------------|------------------------|---------------------------|--|--------------|------------------------|
| MW-1 (21-9) | - | 7/27/2011 | 409,583.8 | 4,405,672.2 | 3,396.3 | 472 | 451 | 9.875 | 4 | 333 | 343 | Quaternary alluvium and playa | 24.9* | 3,421.2 |
| | | | | | | | | | | 385 | 395 | | | |
| | | | | | | | | | | 410 | 430 | | | |
| 108770 | USGS | 9/15/2009 | 410,472.9 | 4,400,461.4 | 3,383.4 | 50 | 50 | 6.625 | 2 | 45 | 50 | Quaternary playa | 14.4 | 3,369.0 |
| 108771 | USGS | 9/16/2009 | 410,472.9 | 4,400,461.4 | 3,383.4 | 15 | 15 | 6.625 | 2 | 10 | 15 | Quaternary playa | 7.4 | 3,376.0 |
| 109435 | USGS | 3/19/2009 | 412,051.3 | 4,402,339.5 | 3,383.1 | 9.625 | 9.625 | 4 | 1 | 5.625 | 9.625 | Quaternary playa | 2.8 | 3,380.3 |
| 109491 | USGS | 3/17/2009 | 410,176.1 | 4,400,776.2 | 3,384.4 | 10 | 10 | 4 | 1 | 5 | 10 | Quaternary playa | 4 | 3,380.4 |
| 109574 | USGS | 3/10/2009 | 408,538.8 | 4,398,347.5 | 3,384.4 | 24.5 | 24.5 | 6.625 | 2 | 19.5 | 24.5 | Quaternary alluvium and playa | 0 | 3,384.4 |
| 21832 | Phillips Petroleum Company | 4/15/1978 | - | - | - | 200 | 200 | 4.75 | 1 | N/A | N/A | Quaternary alluvium and playa | UNK | - |
| 21833 | Phillips Petroleum Company | 4/1/1978 | - | - | - | 200 | 200 | 5.125 | 1 | N/A | N/A | Quaternary alluvium and playa | UNK | - |
| 23087 | Nufuels Corps. | 6/30/1981 | - | - | - | 1,460 | 151 | UNK | UNK | N/A | N/A | Quaternary alluvium | 105 | - |
| 23748 | Nufuels Corps. | 7/19/1981 | - | - | - | 500 | 160 | 8.75 | 6.625 | N/A | N/A | Quaternary alluvium and playa | 8 | - |
| 21834 | BLM | n/a | - | - | - | 300 | 300 | 5.625 | 1.25 | N/A | N/A | Quaternary alluvium | UNK | - |
| 22-8B | Ormat | 7/27/2012 | 407,743.9 | 4,405,476.7 | 3,473.0 | 1,000 | 274 | 3.895 | 4.5 | - | - | Quaternary alluvium | 8.75 | 3,464.3 |
| 22D-8 | Ormat | 8/1/2019 | 407,755.0 | 4,405,482.0 | 3,481.6 | 4,010 | 1,342 | 8.5 | 7 | N/A | N/A | Quaternary alluvium | 40 | 3,441.6 |
| 23-8 | Ormat | 10/20/2015 | 407,916.9 | 4,405,313.3 | 3,462.8 | 4,700 | 829 | 3.895 | 4.5 | - | - | Triassic siltstone | 262.0* | 3,724.8 |
| 23A-8 | Ormat | 3/2/2016 | 407,890.7 | 4,405,290.2 | 3,458.1 | 4,758 | 2,095 | 14.75 | 16 | - | - | Triassic slate and siltstone | 139 | 3,331.0 |
| 24(13)-8ST2 | Ormat | 9/21/2017 | 407,734.1 | 4,404,987.9 | 3,477.2 | 4,800 | 3,394 | 8.5-13 | 9.625-13.375 | - | - | Triassic slate and Jurassic granodiorite | 92 | 3,404.0 |
| 24A-8 | Ormat | 04/2016 | 407,729.0 | 4,404,984.4 | 3,483.1 | 750 | 151 | 3.895 | 4.5 | - | - | Quaternary alluvium | 142.9* | 3,626.0 |
| 86-7 | Ormat | 8/9/2012 | 407,325.9 | 4,404,624.4 | 3,535.6 | 1,000 | 293 | 3.895 | 4.5 | - | - | Quaternary alluvium | 174.1* | 3,709.7 |
| 42(12)-9 | Ormat | 10/26/2011 | 410,009.1 | 4,405,383.9 | 3,388.6 | 7,442 | 3,721 | 12.25 | 13.375 | - | - | Tertiary tuff | 273.5* | 3,662.1 |
| 75-4 | Ormat | 1/21/2017 | 410,548.9 | 4,406,436.8 | 3433.0 | 5,476 | 2,493 | 12.25 | 13.375 | - | - | Jurassic granodiorite and gabbro | 142 | 3291 |

Data Source for well completion information: Nevada Division of Water Resources, Well Logs and Well Log Database, 2019; and Ormat (2019)

Coordinates in NAD 1983 UTM Zone 11N

* Indicate water level in feet above ground surface. Calculated from gauge pressure.

** NDWR Well Log ID Number, or Ormat ID Number

ft amsl feet above mean sea level

ft bgs feet below ground surface

in. inches

m meters

N/A No screened interval or information not provided in Driller's Report

SWL static water level

TOC top of casing

UNK Information not provided in Driller's Report

| Table M2. Summary of Hydraulic Responses during Flow Testing | | | | | | | | |
|--|----------------|--------|-------|----------------|-----------------------|---------|------|------------------|
| Well ID | Pressure (psi) | | | | Depth to Water (fbgs) | | | |
| | P _o | Min P | ΔP | P _F | SWL | Max DTW | ΔDTW | DTW _F |
| 23-8 | 113.4 | 105 | 8.4 | 112.85 | - | - | - | |
| 24A-8 | 61.8 | 59.65 | 2.15 | 61.1 | - | - | - | |
| 42-9 | 118.49 | 104.95 | 13.54 | 116.2 | - | - | - | |
| 86-7 | 75.35 | 67.15 | 8.2 | 68.5 | - | - | - | |
| 22-8B | - | | - | - | 8.75 | 16 | 7.25 | 14.15 |

- P_o Original pressure = pressure recorded prior to flow testing
- Min P Minimum pressure recorded during flow testing
- ΔP Difference between P_o and Min P
- P_F Final pressure = pressure recorded after completion of flow testing
- SWL Static water level = water level recorded prior to flow testing
- Max DTW Maximum depth to water measured during flow testing
- ΔDTW SWL - Max DTW
- DTW_F Final DTW = depth to water recorded after completion of flow testing

This page intentionally left blank.